










SYNTHETIC SLINGS

FLAT WEBBING SLINGS

Flat Webbing Slings are manufactured to the specifications of Australian Lifting Centre & according to Australian Standard AS1353.1. Fabricated using 100% high tenacity polyester yarn and sewn with 2ply webbing. Durable and specially woven, 100% polyester with standard folded eyes that incorporates eye wear padding to provide maximum protection around the eyes. Each Sling is proof tested, individually serial numbered, tagged and complete with Test Certificates.

Note: In stock up to 20t, other variations available upon request

WORKING LOAD LIMITS

COMPLIES AS 1353		VERTICAL	CHOKE	BASKET	30°	60°	90°	120°	60°	60° CHOKE
FLAT SLINGS										
Colour Code	WLL	Vertical	Choke	Basket	30°	60°	90°	120°	60°	60° Choke
LOAD FACTOR		L = 1.0	L = 0.8	L = 2.0	L = 1.9	L = 1.7	L = 1.4	L = 1.0	L = 1.7	L = 1.38
7201 (length)	1.0	1.0	0.8	2.0	1.9	1.7	1.4	1.0	1.7	1.3
7202 (length)	2.0	2.0	1.6	4.0	3.8	3.4	2.8	2.0	3.4	2.7
7203 (length)	3.0	3.0	2.4	6.0	5.7	5.1	4.2	3.0	5.1	4.1
7204 (length)	4.0	4.0	3.2	8.0	7.6	6.9	5.6	4.0	6.9	5.5
7205 (length)	5.0	5.0	4.0	10.0	9.5	8.6	7.0	5.0	8.6	6.9
7206 (length)	6.0	6.0	4.8	12.0	11.4	10.3	8.4	6.0	10.3	8.2
7208 (length)	8.0	8.0	6.4	16.0	15.2	13.8	11.2	8.0	13.8	11.0
7210 (length)	10.0	10.0	8.0	20.0	19.0	17.3	14.1	10.0	17.3	13.8
7220 (length)	20.0	20.0	16.0	40.0	38.0	34.0	28.0	20.0	34.0	27.0

Larger tonnages supplied, however, current standard does not cover larger than 10 tonne.

