

LANO-FORM

Ready to use Formwork | Precast | Tilt Panel Concrete release Agent



Features

- Non DG
- Ready to use
- Safe on rubber and polystyrene
- Non staining
- Compatible with most coating systems

Contents

Lanolin (a natural product), blended with an evaporative carrier & surfactant. Mixes with water.

Usage Examples

- Concrete release agent for formwork, precast and tilt panel
- For use on form surfaces including steel, timber, plywood, plastic & fibreglass
- Bond breaker
- Excellent performance with specialised and geo-polymer concrete
- Extends the life of timber and metal moulds
- Protection of equipment from concrete and paint overspray
- Can be used to lubricate and protect jacks & fittings
- Safe for environmentally sensitive areas and waterways

Preparation

- Shake 20L container before using or decanting
- Agitate 200L drum with mechanical stirrer or air hose system before use or decanting
- Ensure surface is clean and dry
- Product is ready to use, no dilution is required
- Product can be decanted into spray applicators. Good quality applicators are recommended for a fine, even coverage
- Lano-Form™ can be applied after setting polystyrene block outs

Application

- For best results it is recommended that Lano-Form™ be applied by spray application
- Coverage rate is approximately 20-25m² per litre
- Only a very fine mist is required
- For formwork, ensure a light and even coverage. Only one coat is required
- No cleaning required between pours, simply spray, pour, strip and repeat
- When using as a bond breaker, apply the top cured panel in 2 even diagonal opposing coats
- In extreme heat, the panels can be sprayed with water before Lano-Form™ is applied, this reduces the amount of Lano-Form™ absorbed by the cured panel

Storage & Transport

- This product is classified as non-Dangerous Goods
- Keep in cool, dry, well ventilated place
- Keep out of reach of children
- Shelf life is approximately 2 years from manufacture date (See Best Before date label on container)

Removal

- If using to protect equipment from overspray and you wish to remove; or you simply wish to remove Lano-Form™, use Lanotec Citra-Force™

Certifications

- AS4020 Certification - for use in contact with drinking water - testing conducted by NATA certified laboratory
- Global green Tag Certified as an environmentally sustainable product

Always read
entire label
before using
product

For safe handling of this product, please consult the Safety Data Sheet (SDS)
Lanotec Australia PO Box 850, Park Ridge, QLD Australia 4125