

STEEL SEAL™ (SS)

Corrosion Inhibitor - derived from natural & sustainable ingredients

**Features**

- High resistance to acids and salts
- Resists wash off
- Non Evaporative

Contents

Lanolin (a natural product), blended with an evaporative carrier to enable ease of application and enhance penetration.

Usage Examples

- 4WD and Light Vehicle underbody & chassis rails protection
- Protection of jet skis, trailers and all marine motors
- Sea preparation
- Chemical storage facilities and equipment protection
- Agricultural vehicles including boom sprayers & fertiliser spreaders
- Drill pipe protection including threads & internal casings
- Electrical component protection - non conductive to 41kV

Preparation

- Best applied to dry, clean surfaces
- Steel-Seal (SS) can be sprayed to corrosive surfaces to stop further corrosion
- Remove sources of ignitions, voltage and flame until solvent evaporates (approximately 1 hour).

Storage & Transport

- Aerosol classified as Dangerous Goods for transport and storage (UN 1950; DG 2.1 2YE)
- All the other sizes are not classified as DG
- Keep in cool, dry, well ventilated place
- Keep out of reach of children
- Shelf life - virtually indefinite if kept sealed in reasonable conditions

Application

- Shake container to ensure product is mixed correctly.
- Colder climates will require extra agitation.
- Lanotec Steel-Seal can be applied via spray, brush or roller.
- Allow approximately one hour before any equipment is subject to water.

Note: This product has been classified as supplied. When used as directed, and the volatile substances have completely evaporated, the residue is non hazardous (non combustible). Refer to SDS for Lanotec Type A Grease for safety guidance on expected product residual. **NOT RECOMMENDED** for new galvanised surfaces, for information on other Lanotec products better suited to this application, please contact Lanotec or visit our website to find the contact details of the State Manager in your region.

**Always read
entire label
before using
product**

For safe handling of this product, please consult the Safety Data Sheet (SDS)
Lanotec Australia PO Box 850, Park Ridge, QLD Australia 4125